

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
6 October 2005 (06.10.2005)

PCT

(10) International Publication Number
WO 2005/093445 A1

(51) International Patent Classification⁷: **G01R 31/311**

(21) International Application Number:
PCT/IB2005/000755

(22) International Filing Date: 23 March 2005 (23.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0406665.0 25 March 2004 (25.03.2004) GB

(71) Applicant (for all designated States except US):
MELEXIS NV [BE/BE]; Microelectronic Integrated
Systems, Rozendaalstraat 12, B-8900 Ieper (BE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **BERGMANN, Peter**
[DE/DE]; c/o Melexis GmbH, Haarbergstrasse 67, 99097
Erfurt (DE).


(74) Agents: **CHURCH, Simon** et al.; Wilson Gunn Skerrett,
Charles House, 148/9 Great Charles Street, Birmingham
B3 3HT (GB).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,
ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

[Continued on next page]

(54) Title: TESTING INTEGRATED CIRCUITS



(57) Abstract: A testing apparatus for a radiation sensing integrated circuit comprises a load board (101), a test socket (102), suitable for the device under test DUT (103), and a plunger (104). A radiation source (107) is provided on the load board (101) adjacent to the test socket (102). The radiation source (107) generates radiation for testing the response to stimulus of the radiation sensing element of the DUT (103). To enable the sensing element of the DUT (103) to be exposed to the radiation, a pathway (108) is provided through plunger (104). The pathway (108) has a U-Shape with the end of one side of the U being adjacent to the radiation source (107) and the other end of the U being adjacent to the sensing element of DUT (103). Prisms (105, 106) are mounted at the base of each side of the U so as to reflect incident light along the pathway (108), such that radiation entering the pathway (108) from the radiation source (107), travels along the U and exits the other end of the U where it is then incident upon the radiation sensing element of DUT (103).



FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*